

Test Report No. AJFS1906005265FF Date: JUN.13, 2019

SINTRONES TECHNOLOGY CORP.

2F.-3, NO.738, ZHONGZHENG RD., ZHONGHE DIST., NEW TAIPEI CITY 235, TAIWAN (R.O.C.)

The following sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion. results apply to the sample as received.

Product Description: IN VEHICLE COMPUTER

SGS Ref No.: HU50002/2019

Manufacturer/Vendor: SINTRONES

Country of Origin: TAIWAN

Style/Item No.: VBOX-3XXX-XXXXX

Test Requested:

EN 45545-2:2013+A1:2015 Railway applications—Fire protection on railway vehicles Part 2: Requirements for fire behaviour of materials and components, and testing according to Table 5 — Material requirement sets (R25)

Test Results: -- See attached sheet --

Test Period:

Sample Receiving Date : JUN.06, 2019

Test Performing Date : JUN.06, 2019 TO JUN.13, 2019

Signed for and on behalf of SGS-CSTC Co., Ltd. Anji Branch

Allen Zou Lab Manager



Page 1 of 3



Test Report

No. AJFS1906005265FF

Date: JUN.13, 2019

Page 2 of 3

I. Description of Test specimens

Description	PCB board
Color	Green
Sample size	40mm×40mm×1.5mm

II. Summary of test results

Requirement set (used for)	Test method reference	Parameter Unit	Test results *
R25	T16	Glow Wire	850
(EL9)	EN 60695-2-11	Temperature, °C	

^{*} For the test details, please see the appendix of this test report.

III. Conclusion

According to the test results, the submitted sample **meets** the requirements of R25 (detailed in Table 5 of EN 45545-2:2013+A1:2015) for **HL3** Hazard Level Classification.

Test Criteria, EN 45545-2:2013+A1:2015, Table 5, Material requirement sets, R25

Short name of requirement set (used for)	Test method reference	Parameter Unit	Requirement Definition	HL1	HL2	HL3
R25 (EL9)	T16 EN 60695-2-11	Glow Wire Temperature °C	Minimum	850	850	850

Statements:

This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included.

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

The test results relate only to the specimens of the product in the form in which were tested.

To be continued...



Jaless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed worled, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/ferms-e-Document.aspx. taken to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is divised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of items of the company's sole responsibility is to its Client and this document does not exoneate parties to a ransaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisffication of the content or exercising in the company of the sample of the company and the company of th



Test Report

No. AJFS1906005265FF

Date: JUN.13, 2019

Page 3 of 3

APPENDIX: T16 EN 60695-2-11:2014 Fire hazard testing—Part 2-11: Glowing/hot-wire based test methods Glow-wire flammability test method for end-products

1. Conditioning

Prior to testing, the sample was conditioned 24 hours at temperatures of 15~35°C and at a relative humidity of 45~75%.

At time to testing, Temperature between 15°C ~ 35°C and Relative humidity less than or equal to 75 %.

2. Test results

Temperature of the glow-wire ($^{\circ}$ C)		850	850
Duration (t _i) from the beginning of tip application up to the time at which the test specimen or the specified layer placed below it ignites (s)		NI	NI
Duration (t_e) from the beginning of tip application up to the time when flames extinguish during or after the period of application (s)	NI	NI	NI
Whether the test specimen extinguishes by virtue of most of the flaming material being withdrawn with the glow-wire	No	No	No
Whether ignite the specified layer placed underneath the test specimen or not	No	No	No
Whether the test specimen is totally burned	No	No	No
Observations: None			

Remark: NI--- Not ignition

In accordance with test results, the submitted sample: **GWEPT: 850**

Photo Appendix:



SGS authenticate the photo on original report only

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excentate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced accept in full, without prior written approval of the Company. Any unauthorized alteration, forgety or faisficiation of the content or results shown in this lest report refer only to the sample (s) tested and such sample (s) are retained for 30 days only.