

IBOX-650P-IP66


NVIDIA® Jetson AGX Orin Fanless Edge AI Computer



- NVIDIA® Jetson AGX Orin™ SoM with 2048 CUDA Cores
- IP66 Design (Waterproof and Dustproof) for Harsh Environment
- 1 x 10 GbE, 2 GbE with PoE via Phoenix Contact® M12 IP67 Connectors
- 2 x CAN FD
- 2 x RS-232/422/485*, 4 x DI/4 x DO*
- Supporting 4 x GMSL-2 Cameras (via FAKRA Connectors)
- 9 ~ 60VDC Input with Built-in Smart Ignition Power Management
- -25 ~ 70°C Operating with Fanless Design
- Patented Design of Emergency Backup Battery*

*This is a customized specification. If you have any needs, please contact our sales representative.

Edge AI Application



Specifications

System

Module

- NVIDIA® Jetson AGX Orin™ 64GB (2048 CUDA® cores GPU + 12-core Arm Cortex-A78AE CPU + 64 GB LPDDR5)
- NVIDIA® Jetson AGX Orin™ 32GB (1792 CUDA® cores GPU + 8-core Arm Cortex-A78AE CPU + 32 GB LPDDR5)

Network

- Marvell® Industrial 10GbE, Intel® Industrial 2.5GbE

Security

- Platform Security Controller (PSC), Security Engine (SE)

Interface

Ethernet

- 1 x 10GbE, 2 x 2.5GbE w/ 2 x IEEE 802.3at PoE PSE Class 4 (PoE+ 30 watts) (3 x Phoenix Contact® M12 X-coded connectors)

USB

- 2 x USB Type-A/IP67 connector for USB 3.2
- *One port share 10Gbps bandwidth

Video

- 1 x HDMI® via Type-A w/ IP67

Audio

- 1 x HD Audio output from the HDMI®

Serial Port

- 1 x M12 A-coded connector for RS-232/422/485

CAN Bus

- 2 x M8 A-coded connectors for CAN FD

Mgmt. Port

- 1 x USB Type-C for System Recovery (Device only)

Camera

- 4 x FAKRA-Z connectors for GMSL-2 cameras

SIM Card

- 1 x Nano SIM card slot

Internal Expansion

M.2 Slot

- 1 x M.2 3042/52 Key B slot (USB3.0) with a Nano SIM Card Slot
- 1 x M.2 2230 Key E slot

mPCIe Slot

- 1 x mPCIe Full size slot (USB.2.0 supported)

Storage

Type

- 1 x 64GB eMMC (Built-in within SoM)
- 1 x M.2 2280 Key M slot supports NVMe SSD

Power

Supply Voltage

- 1 x Phoenix Contact® M12 K-coded connector for DC-IN 9~60V

Power Protection

- OCP, OVP, Surge and Reversed Polarity Protection

Power Management

- Ignition Detection with Smart Power Management

RTC Battery

- High-capacity coin cell battery for RTC

UPS (Option)

- Backup battery for system power backup

Software

Operating System / BSP

- NVIDIA® JetPack 6.2 or above (Jetson Linux and NVIDIA® development tools included)

Environmental

- Operating Temp.**
- -25°C ~ 70°C (-13°F ~ 158°F), ambient w/ 0.6m/s airflow
 - * Operating temp. varies by accessories installed.
- Storage Temp.**
- -40°C ~ 80°C (-40°F ~ 176°F)
- Relative Humidity**
- 10% RH – 90% RH (non-condensing)
- Vibration (with SSD)**
- MIL-STD-810H, Method 514.8, Procedure I, Cat.4 (Operating)
 - IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis
- Shock (with SSD)**
- MIL-STD-810H, Method 516.8, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD (Operating)


Certification / Standard

- CE, FCC Class A, E-Mark, ECE R118, EN50155, EN45545-2 (R25)

Mechanical

- Construction**
- Aluminum Alloy
- Ingress Protection**
- IP66
- Thermal Design**
- Fanless Passive Cooling
- Mounting**
- Wall-mount
- Weight**
- 5100 g
- Dimensions**
- 300 (L) x 190 (W) x 77.5 (H) mm

Dimensions



Ordering Information

Model Number	IBOX-650P-IP66-01-JAO64	NVIDIA®Jetson AGX Orin™ 64GB / VDB-101 / 4 x GMSL-2 / 2 x PoE / 1 x 10GbE
	IBOX-650P-IP66-01-JAO32	NVIDIA®Jetson AGX Orin™ 32GB / VDB-101 / 4 x GMSL-2 / 2 x PoE / 1 x 10GbE
	IBOX-650P-IP66-JAO64-LE	NVIDIA®Jetson AGX Orin™ 64GB / 2 x PoE / 1 x 10GbE
	IBOX-650P-IP66-JAO32-LE	NVIDIA®Jetson AGX Orin™ 32GB / 2 x PoE / 1 x 10GbE
Description	NVIDIA® Jetson AGX Orin™ w/ 1 x 10GbE / 2 x 2.5GbE / 1 x HDMI / 2 x CAN FD / DC 9-60V / IP66 Edge AI Computer	
State of Origin	Made in Taiwan	

* The system BSP is pre-installed in the internal 64GB eMMC.
Jetson Orin SoM Lifecycle is available through January 2032.

Optional Accessories

Storage	M.2 2280 NVMe SSD 240GB / 480GB / 960GB
Wi-Fi	M.2 2230 Wi-Fi Module
WWAN	M.2 3042/52 WWAN Modem
GNSS	mPCIe GPS Module
Battery (UPS)	BAT-2300v2 (Operating Temp. : -10°C ~ 60°C (-4°F ~ 140°F))
Power Adapter	150W 100-240VAC to 12VDC Power Adapter
Camera*	SINTRONES - VCM-1020G2 Series (Sony IMX390 2MP, 63.9°, GMSL-2, 63.9°/120°/186°)
	Stereolabs - ZED X Stereo
	e-con System - STURDeCAM25 / e-con System - STURDeCAM81
	oToBrite - otoCAM223 / oToBrite - otoCAM260

*BSP versions may vary depending on supported GMSL cameras. All specifications are subject to change without notice.